Ratings and Characteristic Curves

Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instaneous Forward Characteristics




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surage Current







Fig.6- Typical Transient Thermal Impedance






	Tape/Reel,13”reel	3000PCS/Reel 30000PCS/Carton



A	1.35	1.75	53	68
C	0.25	0.55	9.8	21.6
D	9.4	9.8	370	385
E	8.4	8.8	330	346
E_1	9.8	10.2	385	401
L	0.85	1.25	33	49
e	4.9	5.3	193	209
b	1.25	1.55	49	61
∠	10°			



The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website https://www.yfwdiode.com, or consult YFW sales office for further assistance.