Marking Code	

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Value	Unit
Input Voltage	V_I	30	V
Power Dissipation 1	P_D	800	mW
Operating Temperature	T_J	- 20 to + 120	
Storage Temperature Range	T_{STG}	- 55 to + 150	

(1) 15 mm X 25 mm X 0.7 mm alumina ceramic board, Ta ≤ 25

Electrical Characteristics (Ta=25°C)

(Unless otherwise specified, 0 ≤ T_J ≤ 125 , V_I = 14 V, I_O = 40 mA, C_I = 0.33 µF, C_O = 0.1 µF)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Output Voltage	V_O	T_j = 25 ℃	7.7	8	8.3	V
		10.5 V ≤ V_I ≤ 23 V, 1 mA ≤ I_O ≤ 40 mA	7.6	-	8.4	V
		V_I = 14 V, 1 mA ≤ I_O ≤ 70 mA	7.6	-	8.4	V
Line Regulation	Reg_{line}	10.5 V ≤ V_I ≤ 23 V, T_j = 25 ℃	-	-	175	mV
		11 V ≤ V_I ≤ 23 V, T_j = 25 ℃	-	-	125	
Load Regulation	Reg_{load}	1mA ≤ I_O ≤ 100 mA, T_j = 25 ℃	-	-	80	mV
		1mA ≤ I_O ≤ 40 mA, T_j = 25 ℃	-	-	40	
Quiescent Current	I_Q	T_j = 25 ℃	-	-	5.5	mA
Quiescent Current Change	ΔI_Q	12 V ≤ V_I ≤ 23 V, I_O = 40 mA	-	-	1.5	mA
		V_I = 14 V, 1 mA ≤ I_O ≤ 40 mA	-	-	0.1	
Output Noise Voltage	V_N	10 Hz ≤ f ≤ 100 KHz, T_j = 25 ℃	-	60	-	µV
Ripple Rejection	RR	f = 120 Hz, 12 V ≤ V_I ≤ 22 V, T_j = 25 ℃	39	-	-	dB
Dropout Voltage	V_{Drop}	T_j = 25 ℃	-	1.7	-	V

Typical Characteristics (continued) (V_{OUT}=8.0V,T_J=25°C, unless otherwise specified)



The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website https://www.yfwdiode.com, or consult YFW sales