


TO-252(D-PAK)

High current capability
Low forward voltage drop
High surge capability
High temperature soldering guaranteed
Mounting position: any
Lead free in comply with EU RoHS 2011/65/EU directives

Case: TO-252(D-PAK)
Terminals: Solderable per MIL-STD-750, Method 2026
Approx. Weight: 0.32g /0.011oz

Maximum Repetitive Peak Reverse Voltage		45	
Maximum RMS voltage		31.5	
Maximum DC Blocking Voltage		45	
Maximum Average Forward Rectified Current		10	
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed On Rated Load (JEDEC method)		150	
Typical Junction Capacitance (1)		620	
Typical Thermal Resistance (2)		45	
Operating Junction Temperature Range		-55 ~ +150	
Storage Temperature Range		-55 ~ +150	

( )
( )

Breakdown voltage per diode		=0.5mA	45	-	-	
Instantaneous forward voltage per diode		=2A	-	0.30	-	
		=5A =25°C	-	0.38		
		=10A	-	0.42	0.50	
		=2A	-	0.25		
		=5A =125°C	-	0.35	-	
		=10A	-	0.38		
Reverse current per diode		=36V	-	5	-	
		=45V =25°C	-	-	50	
		=125°C		5.5	-	

Fig.1 TYPICAL FORWARD CURRENT DERATING CURVE





Fig.3 Typical Forward Characteristic



Marking Diagram

Ordering information

Model name	Package	Unit Weight	Base Quantity	Packing Quantity

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website https://www.yfwdiode.com, or consult YFW sales office for further assistance.