- Fast switching speed
- High conductance
- High reverse breakdown voltage rating
- Surface mount package ideally suited for automatic insertion

- Small signal swi

Parameter	Symbol	Test conditions	MIN	Typ	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)R}$	I_R=150μA	350			V
Reverse voltage leakage current	I_R	V_R=240V V_R=240V T_j=150		30 35	100 100	nA μA
Forward voltage	V_F	I_F=20mA I_F=100mA I_F=200mA		0.78 0.93 1.03	0.87 1.0 1.25	V
Total capacitance	C_T	V_R=0V,f=1MHz		1.0	5.0	pF
Reverse recovery time	t_{rr}	I_F=I_R=30mA, I_{rr}=0.1×I_R,R_L=100Ω			50	ns




Fig. 1 Power Derating Curve, total package

Fig. 2 Typical Forward Characteristics, per element




Fig. 3 Typical Reverse Characteristics, per element

vs. Reverse Voltage, per element

Ordering information

Package	Packing Description	Base Quantity	Packing Quantity
SOT-23	Tape/Reel,7”reel	3000pcs/Reel	24000PCS/Box 120000PCS/Carton

Package Dimensions

SOT-23

Dim.	Millimeter (mm)		mil	
	Min.	Max.	Min.	Max.
A	0.9	1.15	35	45
A1	0.1		3.9	
bp	0.38	0.48	15	19
C	0.09	0.15	3.54	5.9
D	2.8	3.0	110	118
E	1.2	1.4	47	55
E	1.9		75	

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which