4.0A Single-Phase GLass Passivated Fast Recovery Bridge Rectifiers

Reverse Voltage - 1000 V

Forward Current - 4.0A

FEATURES

- Glass passivated junction
- The plastic material used carries Underwriters Laboratory flammability recognition 94V-0
- Suge overload ratings to 120 amperes peak
- Ideal for printed circuit board application
- High temperature soldering guaranteed 265°C/10 seconds at 5 lbs(2.3kg)tension

MECHANICAL DATA

- Case:HBS
- Terminals:Platde leads solderable per MIL-STD-750, Method 2026
- Polarity:Polarity symbols molded or Marked on body
- Mounting Position:Any
- Weight:0.015ounce,0.38 grams(approx)

Maximum Ratings & Thermal Characteristics

Ratings at 25 ambien

Ratings and Characteristics Curves

(TA = 25 unless otherwise noted)

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website https://www.yfwdiode.com, or consult YFW sales office for further assistance.